



Fire brigade
Liquidation
of Accidents



Transport
& Logistics
Industry



Construction
Hobby



Water
& Forest
Sea



Collapsible spill bund Eccotarp ET

This collapsible spill bund is designed for a quick response to accidental leaks of water, oil-based products and chemicals. The spill bunds are delivered in several sizes. It is also possible to use the bigger models both as large volume containers and to capture spills when siphoning fuel from refuelling trucks.



- ▶ Possibility of fitting round any object
- ▶ Immediately ready to be used even in inaccessible areas
- ▶ Easy handling
- ▶ Maximum carrying capacity 200 kg
- ▶ Built-in level indicator to show the quantity of retrieved liquid
- ▶ Possibility of adding of drain hole and ball valve



**Quickly and easily converts
into a pool, ready to capture all
spills and leaks**



Examples of uses

Placing of handling belts is easy and fast thanks to the new type of hooks

Possibility of adding of drain hole and ball valve

Protective insert

Securing of the corner of the bund by a yellow hook

The bag is a standard part of the product

Product variants

The **XL DECON** spill bund with its lower sidewalls is especially suitable for emergency decontamination of people. The reinforcements in the sidewalls of the **EASY PACK** are multi-segmented, so the bund folds better around any obstacle and it can be folded into a smaller pack.


The **SHALLOW** version with its extremely low profile design can either be used in inaccessible areas, especially in narrow spaces with low headroom, or as a spill collecting tray to ensure safe filling and emptying of vessels.

Technical details

Due to reinforcements in the side walls the spill bunds are rigid and self-supporting. They are made from thick fabric with a protective proofing layer (PES/PVC 680 g/m²). They are resistant to oil-based substances, acids and alkalis at temperatures between -30°C and +70°C (see. Chemical resistance certificate in the relevant chapter at the end of catalogue). New handling belts – with a maximum carrying capacity 200 kg and safety fastening hooks at both ends – are used for manipulation.

The protective pad and special liner which are delivered as accessories considerably enhance the durability of the spill bund.

The product is protected by registered utility model (technical patent) no. 22118 lodged with the Industrial Property Office.



Type	ET 01 S	ET 02 M	ET 03 L	ET 04 XL	ET 041 XL DECON	ET 051 XXL EASY PACK	ET 06 SHALLOW
Dimensions/basin (mm)	350 × 700 × 125	700 × 700 × 175	1000 × 1000 × 200	1500 × 1500 × 425	1500 × 1500 × 225	2000 × 2000 × 425	1240 × 840 × 70
Capacity (l)	25	75	175	900	450	1600	50
Dimensions/unfolded (mm)	950 × 350	1050 × 700	1400 × 1000	2350 × 1500	1950 × 1500	2850 × 2000	1380 × 840
Pack Size (mm)	560 × 300 × 120	560 × 300 × 120	710 × 410 × 120	1200 × 560 × 90	1000 × 560 × 90	930 × 740 × 90	450 × 450 × 80
Weight (kg)	2,0	3,3	5,6	17,8	9,8	23,2	2,9
Accessories:							
Bag (mm)	260 × 520	345 × 580	500 × 810	600 × 1240	600 × 1050	800 × 1050	350 × 450
Pad (mm)	1000 × 500	1300 × 1300	1300 × 1300	2200 × 2200	2200 × 2200	2200 × 2200	1300 × 1300
Protective insert ET 11-16	yes	yes	yes	yes	yes	yes	
Drain hole on request D25		yes	yes	yes	yes	yes	
Ball valve on request D25		yes	yes	yes	yes	yes	
Hose with outlet on request D25		yes	yes	yes	yes	yes	

Specifications

One time use, protective inserts for all sizes (please see the Chemical resistance certificate)