

Drum & IBC Store - DPU8-2

Backed by our 20 year structural guarantee*

A 2mm pressed steel welded body construction provides the structural strength for this unit, while the roof which is fitted with lifting eyes is manufactured from 3mm mild steel. The two easy glide sliding doors are constructed from 2mm mild steel and are fitted with a central lock and padlock points (padlocks not supplied).

Constructed from 3mm mild steel, the sump is fully seam welded and fitted with pallet support beams for the pallets to sit on. The sump as you would expect complies fully with all current UK regulations relating to sump capacities and the underside is fitted with plinths to eliminate contact with ground and reduce the risk of corrosion. Prior to painting the unit is fully shot blasted to provide a clean and keyed surface.



Photo model shown with optional vents and grid mesh

This model can hold up to 8 x 205ltr drums or 2 x 1000ltr IBC's and will accommodate standard 1200mm x 1200mm, 1200mm x 1000mm and 1200mm x 800mm pallets.

*Full details available on request

SPECIFICATION	
External size	3000mm L x 1500mm W x 2403mm H at the highest point of the unit
Number of containers	8 x 205ltr or 2 x 1000ltr – side by side
Sump capacity	1125ltr
Colour	Green RAL 6029
Tare weight	1050kg
Type of doors	2 sliding
Access aperture	1371mm W x 1967mm H
Paint specification	A high build, quick drying primer/topcoat paint specifically designed for use directly on to metal or bare steel, this paint contains zinc phosphate anti-corrosive pigments and is applied with a minimum dry film thickness of 75 microns.

Chargeable Options:

- Air vents
- Galvanised steel grid mesh
- Galvanised steel pallet channels

Please notify us at the time of ordering if you require any of these options.

