

# TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

## HexaDyn®

ARTICLE CODE


### BR202-H

Oil absorption capacity L/KG\*: **139**  
Water absorption capacity L/KG\*: **0**  
Net weight: **9.6**  
Qty / pallet: **15**

\*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

## APPLICATION

<b>BLUE HYDROPHOBIC</b>	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
<b>ROLLS</b>	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
<b>HEAVY WEIGHT</b>	Superior absorption capacity for pollutions treatment

## WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mess to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

## ADDITIONAL INFORMATION

**TRANSPORT:** No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

**SECURITY:** No specific risk. For further information, please refer to the material safety data sheet.

**STORAGE:** Store in a dry and cool place.

**DISPOSABILITY:** The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

## SPECIAL REMARKS

*The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.*

13/09/2016 16:20:31