

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GM313-H

Oil absorption capacity L/KG*:	150
Water absorption capacity L/KG*:	117
Net weight:	16.668
Qty / pallet:	8

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Mat 1.20X30M

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used proactively, saving you money
- Unlike granules it's easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.