

OLIESUG DOOR BOOM

Instructions for use

I. Putting the Door Boom in place

1. Take the complete door boom out of the storage cannister.
2. Put the door boom in door or gate way; the large diameter tube should always face the liquid to be off.
3. Lift filler neck by approx. 50 cm.
4. Fill in liquid, e.g. water, (no pressure necessary); fill small and large diameter tube simultaneously.
5. Fold in excessive tube material

II. How to empty the Door Boom

1. Lower filler neck. Lift door boom at tube end, empty and roll it up. Do not pull as long as tube is still filled with water.
When used as collecting basin, first fill the dangerous liquids in appropriate barrels following your official safety instructions and dispose as required. For safety reasons also the PE tube should be disposed off according to regulations.
2. After use and disposal of the PE tube connect replacement tube to filler section and repeat the whole in your storage cannister.

III. Visual Inspection

Check door boom with regard to damages and fading out in a 6 month time. Replace tube as necessity arises.

IV. Technical Characteristics/Resistance to Chemicals

For technical properties of Polyethylene products such as resistance to chemicals and other substances, mechanical influences, UV-light and resistance to various temperatures please refer to our „stability list“.

V. Special Hint

The Door Boom is a boom, which is subject to damages through mechanical influences.
Therefore the boom has to be kept ready for use at any time in its original state.