



High capacity tank with collapsible structure

The tank is suitable, for example, for helicopter firefighting using the bambi bucket or for repumping materials at places difficult to reach.



- ▶ Rapid assembly
- ▶ Low weight
- ▶ Simple and robust structure is made of a light alloy and stainless steel
- ▶ Packed construction takes minimal space
- ▶ Volume of 5 000–50 000 litres



Utility water reservoir
or a collection tank
for hazardous substances



The whole tank can be set up by a single person in several minutes

Ball valve C52

Process of tank draining so as there remains no water

Accessory: fill elbow

No tools are needed to assemble the tank; its parts are connected with special pegs

Collapsible load-bearing leg for inclined ground

Technical details

The tank is made of a highly resistant PES/PVC material providing the temperature range of use of -30 °C to +70 °C. The material is resistant against chemical and oil substances (see Chemical resistance certificate in the relevant chapter at the end of catalogue), thereby providing enhanced potential of use in environmental accidents. The tank can be filled very quickly using the filling elbow with C52 (B75/other) end piece in the upper part of the structure. A fill/discharge valve (type according to customer's choice) is located in the bottom part of the tank. As an optional accessory, the tank structure can be equipped with a holder of ferrule of fire hose. It is an above-standard construction designed especially for the purpose of firmly anchoring the position of the ball valve with the valve at the bottom of the tank. Thanks to this element, there is no danger of coming out of the holder of ferrule of fire hose of the tank tarpaulin even at full load.

In order to increase the life and the resistance of the tanks we recommend using the protective pad which is a standard part of the product. **The maximum slope of the tank is 8 %!**

Fastening lugs are used to tighten and unfold the bottom of the tank; the structure can be anchored through openings in the footing part

Type	ET TANK 5000	ET TANK 7500	ET TANK 20000	ET TANK 35000	ET TANK 50000
Volume (l)	5000	7500	20000	35000	50000
Diameter (mm)	2300	2700	4200	5500	6600
Height (mm)	1300	1300	1500	1500	1500
Vertical supports/load-bearing legs	6/2	6/2	10/4	12/4	12/4
Package dimensions (mm) and weight of the structure (kg)	300 × 200 × 1350 30	300 × 200 × 1600 30	500 × 200 × 1550 50	500 × 200 × 1550 60	500 × 300 × 1700 70
Package dimensions (mm) and weight of the foil (kg)	300 × 200 × 800 20	300 × 200 × 800 25	400 × 400 × 1000 50	600 × 400 × 1100 70	800 × 500 × 1200 90
Standard accessories					
Transport bag for tank	yes	yes	yes	yes	yes
Transport bag for support structure	yes	yes	yes	yes	yes
Protective pad (mm)	2500 × 2500	3000 × 3000	4500 × 4500	6000 × 6000	7000 × 7000
Optional accessories at extra cost					
Fill elbow C52/B75/other	yes	yes	yes	yes	yes
Ball valve C52/B75/other	yes	yes	yes	yes	yes
Reduction coupling C52/B75/other	yes	yes	yes	yes	yes
Holder of ferrule of fire hose	yes	yes	yes	yes	yes